

Type N F/F Bulkhead Coaxial RF Surge Protector, 700MHz to 1000MHz, Telemetry, DC Pass, 15V, IP67, 20kA, Hybrid, Flange Mount



109-0501W-D

Features

- Surge Current of 20kA
- Max Power 750W
- Frequency Range from 700MHz to 1000MHz
- Passes 2.176MHz Telemetry Signal
- N Female to N Female connectors
- VSWR 1.1:1
- Low Insertion Loss
- Multi-strike capability
- Flange Mount
- CE & RoHS compliant

Applications

- Cellular
- Land mobile radio

Description

RF surge protector (also known as lightning arrester) 109-0501W-D from PolyPhaser, utilizing a patented hybrid protection technology integrating a silicon avalanche suppression diode (SASD) and a MOV and gas tube, enables a quick response to a lightning surge to protect critical hardware while maintaining the RF performance. This RF surge protector component is manufactured in a coaxial in-line design with wide operating frequency range. All PolyPhaser RF surge protector products are available in stock with same day shipping.

Electrical Specifications

Surge Protector Type DC Handling		Hybrid DC Pass		
Description	Minimum	Typical	Maximum	Units
Frequency Range	700		1,000	MHz
Impedance		50		Ohms
VSWR			1.1:1	
Insertion Loss			0.4	dB
Operating Voltage (DC)			15	Volts
Operating Current (DC)			4	A
Input Power, CW			750	Watts
Surge Current			20	kA
Turn On Voltage		16.5		Volts
Throughput Energy			500	uJ

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[Type N F/F Bulkhead Coaxial RF Surge Protector, 700MHz to 1000MHz, Telemetry, DC Pass, 15V, IP67, 20kA, Hybrid, Flange Mount 109-0501W-D](#)

Type N F/F Bulkhead Coaxial RF Surge Protector, 700MHz to 1000MHz,
Telemetry, DC Pass, 15V, IP67, 20kA, Hybrid, Flange Mount



109-0501W-D

Insertion Loss, Max	0.4	dB
---------------------	-----	----

Mechanical Specifications

Size	
Length	3.65 in [92.71 mm]
Width/Diameter	1.73 in [43.94 mm]
Height	3.01 in [76.45 mm]
Weight	1 lbs [453.59 g]
Housing Material and Plating	Aluminum

Configuration

Input Connector	N Female
Output Connector	N Female

Environmental Specifications

Temperature	
Operating Range	-50 to +85 deg C
Ingress Protection (IP) Rating	IP67
Humidity	95%

Compliance Certifications

RoHS Compliant	Yes
CE Compliant	Yes

Plotted and Other Data

Notes:

PolyPhaser protects and increases the reliability of global RF communications networks, including transportation, telecommunications, defense, security and industrial applications, with superior RF surge protection technologies including DC Block, DC Pass and Ultra Low PIM. Backed by responsive service and expert technical support PolyPhaser continually expands its product offering and services to serve engineers' urgent needs for RF components in mission critical communication networks.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Type N F/F Bulkhead Coaxial RF Surge Protector, 700MHz to 1000MHz, Telemetry, DC Pass, 15V, IP67, 20kA, Hybrid, Flange Mount 109-0501W-D](#)

URL:

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. PolyPhaser reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. PolyPhaser does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and PolyPhaser does not assume any liability arising out of the use of any part or documentation.

109-0501W-D CAD Drawing

Row D