

## 2 FT 7/16 to 7/16 M/F 195 Series Low Loss Cable Jumper

### CA195LL033-2FT




#### Configuration

- Connector 1: 7/16 DIN Male
- Connector 2: 7/16 DIN Female
- Cable Type: PPBC-195LL

#### Features

- LMR Equivalent Coax
- Max Frequency 5.8 GHz
- Shielding Effectivity > 90 dB
- 80% Phase Velocity
- Low Insertion Loss
- Double Shielded
- PE Jacket
- One Time Bend Radius of 0.5 Inches



#### Applications

- General Purpose
- Laboratory Use
- Antenna Installations
- Land Mobile Radio & Other Communication Systems
- Cellular & Wi-Fi Systems

#### Description

PolyPhaser CA195LL033-2FT is a 2 foot 7/16 to 7/16 M/F 195 Series Low Loss Cable Jumper is built using high quality components by skilled technicians to ensure a reliable product. The 7/16 Male and 7/16 Female cable jumper connections are designed to industry standard interface dimensions to ensure superior performance. If you have an immediate need, these products are available to ship same day. This high-quality RF coaxial assembly is perfect in many RF Interconnect applications such as LMR, cellular, IoT network, and many other applications. The CA195LL033-2FT 7/16 to 7/16 cable assembly is the perfect companion to PolyPhaser line of RF surge protection devices particularly when used as an antenna jumper cable.

The 195 Series coax used in these 7/16 to 7/16 assemblies is a 0.195 inch diameter coax with a black PE jacket. This cable's foam PE dielectric is low loss material with a VoP of 80% reducing the attenuation when compared to solid dielectric coax cables. PolyPhaser Low Loss 195 Series coax has a solid center conductor and uses a double shield comprised of a wire braid over a foil tape construction providing >90% shielding effectivity. The construction and materials of the CA195LL033-2FT result in a coax cable assembly with 0.5 inch one time bend radius and a repeat bend radius of 2 inches. The cable assembly's combination of 7/16 to 7/16 Male/Female and 195 Series Low Loss Cable supports a maximum operating frequency of 5800 MHz. Detailed specifications for this configuration includes layout drawings and performance and material specifications. All assemblies are design verified and shipped with a certificate of compliance.

Polyolefin heat shrink strain relief boots add additional strength on both ends of this 2 foot assembly. These epoxy filled heat shrinks provide strain relief to help prevent damage from over-bending the assembly ends.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:  
[2 FT 7/16 to 7/16 M/F 195 Series Low Loss Cable Jumper CA195LL033-2FT](#)

## 2 FT 7/16 to 7/16 M/F 195 Series Low Loss Cable Jumper

### CA195LL033-2FT



#### Electrical Specifications

| Description             | Minimum | Typical      | Maximum | Units        |
|-------------------------|---------|--------------|---------|--------------|
| Frequency Range         | DC      |              | 5.8     | GHz          |
| VSWR                    |         |              | 1.5:1   |              |
| Velocity of Propagation |         | 80           |         | %            |
| RF Shielding            | 90      |              |         | dB           |
| Capacitance             |         | 25.4 [83.33] |         | pF/ft [pF/m] |
| Operating Voltage (AC)  |         |              | 2,700   | Vrms         |
| Jacket Spark            |         |              | 5,000   | Vrms         |

#### Specifications by Frequency

| Description           | F1   | F2   | F3   | F4   | F5  | Units |
|-----------------------|------|------|------|------|-----|-------|
| Frequency             | 0.25 | 0.5  | 1    | 2.5  | 5.8 | GHz   |
| Insertion Loss (Max.) | 0.32 | 0.36 | 0.44 | 0.58 | 0.8 | dB    |

##### Electrical Specification Notes:

The Insertion Loss data above is based on the performance specifications of the coax cable and connectors used in this assembly. Insertion Loss is estimated as 0.1 dB per connector.

#### Mechanical Specifications

##### Size

|          |                      |
|----------|----------------------|
| Length   | 24 in [609.6 mm]     |
| Diameter | 0.195 in [4.95 mm]   |
| Weight   | 0.484 lbs [219.54 g] |

##### Cable

|                                      |                     |
|--------------------------------------|---------------------|
| Cable Type                           | PPBC-195LL          |
| Impedance                            | 50 Ohms             |
| Inner Conductor Type                 | Solid               |
| Inner Conductor Material and Plating | Copper              |
| Dielectric Type                      | PE (F)              |
| Number of Shields                    | 2                   |
| Shield Layer 1                       | Aluminum Tape       |
| Shield Layer 2                       | Tinned Copper Braid |
| Jacket Material                      | PE, Black           |
| Jacket Diameter                      | 0.195 in [4.95 mm]  |
| One Time Minimum Bend Radius         | 0.5 in [12.7 mm]    |
| Repeated Minimum Bend Radius         | 2 in [50.8 mm]      |

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:  
[2 FT 7/16 to 7/16 M/F 195 Series Low Loss Cable Jumper CA195LL033-2FT](#)

## 2 FT 7/16 to 7/16 M/F 195 Series Low Loss Cable Jumper

### CA195LL033-2FT



#### Connectors

| Description                       | Connector 1           | Connector 2      |
|-----------------------------------|-----------------------|------------------|
| Type                              | 7/16 DIN Male         | 7/16 DIN Female  |
| Impedance                         | 50 Ohms               | 50 Ohms          |
| Contact Material and Plating      | Spring Bronze, Silver | Silver           |
| Dielectric Type                   | PTFE                  | PTFE             |
| Body Material and Plating         | Brass, Tri-Metal      | Brass, Tri-Metal |
| Coupling Nut Material and Plating | Brass, Tri-Metal      |                  |
| Hex Size                          | 1 1/4 in.             |                  |

#### Environmental Specifications

##### Temperature

Operating Range -40 to +85 deg C

#### Compliance Certifications

#### Plotted and Other Data

##### Notes:

- Values at 25°C, sea level.

PolyPhaser protects and increases the reliability of global RF communications networks, including transportation, telecommunications, defense, security and industrial applications, with superior RF surge protection technologies including DC Block, DC Pass and Ultra Low PIM. Backed by responsive service and expert technical support PolyPhaser continually expands its product offering and services to serve engineers' urgent needs for RF components in mission critical communication networks.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2 FT 7/16 to 7/16 M/F 195 Series Low Loss Cable Jumper CA195LL033-2FT](https://www.polyphaser.com/2-ft-7-16-to-7-16-m-f-195-series-low-loss-cable-jumper-p.aspx)

URL: <https://www.polyphaser.com/2-ft-7-16-to-7-16-m-f-195-series-low-loss-cable-jumper-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. PolyPhaser reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. PolyPhaser does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and PolyPhaser does not assume any liability arising out of the use of any part or documentation.

CA195LL033-2FT CAD Drawing

