

50 FT Type N to Type N M Right Angle/M Right Angle  
600 Series Low Loss Cable Jumper

**CA600LL049-50FT**




**Configuration**

- Connector 1: N Male Right Angle
- Connector 2: N Male Right Angle
- Cable Type: PPBC-600LL

**Features**

- LMR Equivalent Coax
- Max Frequency 5.8 GHz
- Shielding Effectivity > 90 dB
- 87% Phase Velocity
- Low Insertion Loss
- Double Shielded
- PE Jacket
- One Time Bend Radius of 1.5 Inches



**Applications**

- General Purpose
- Laboratory Use
- Antenna Installations
- Land Mobile Radio & Other Communication Systems
- Cellular & Wi-Fi Systems

**Description**

PolyPhaser CA600LL049-50FT is a 50 foot Type N to Type N M Right Angle/M Right Angle 600 Series Low Loss Cable Jumper is built using high quality components by skilled technicians to ensure a reliable product. The Type N Male Right Angle cable jumper connections are designed to industry standard interface dimensions to ensure superior performance. This product is in stock and available for same day shipping. The use of a right angle interface helps when attaching the cable assembly in tight spaces and can reduce strain on the cable/connector interface. This high-quality RF coaxial assembly is perfect in many RF Interconnect applications such as industrial / commercial, laboratory test and measurement, military / defense, and many other RF systems. The CA600LL049-50FT Type N to Type N cable assembly is the perfect companion to PolyPhaser line of RF surge protection devices particularly when used as an antenna jumper cable.

The 600 Series coax used in these Type N to Type N assemblies is a 0.59 inch diameter coax with a black PE jacket. This cable's foam PE dielectric is low loss material with a phase velocity of 87% reducing the attenuation when compared to solid dielectric coax cables. PolyPhaser Low Loss 600 Series coax has a solid center conductor and uses a double shield comprised of a wire braid over a foil tape construction providing >90% shielding effectivity. The construction and materials of the CA600LL049-50FT result in a coax cable assembly with 1.5 inch one time bend radius and a repeat bend radius of 6 inches. The cable assembly's combination of Type N to Type N Male Right Angle/Male Right Angle and 600 Series Low Loss Cable supports a maximum operating frequency of 5.8 GHz. You can find detailed performance specifications in the product datasheet. Processes and procedures are in place to ensure products meet the published specifications.

For additional strength, these Type N Male Right Angle to Type N Male Right Angle cable assemblies have polyolefin heat shrink strain relief boots on both ends of the RF Cable Assembly Jumpers. The heat shrink booting uses a double walled epoxy filled material to prolong the life of the assembly.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:  
[50 FT Type N to Type N M Right Angle/M Right Angle 600 Series Low Loss Cable Jumper CA600LL049-50FT](#)

50 FT Type N to Type N M Right Angle/M Right Angle  
600 Series Low Loss Cable Jumper

## CA600LL049-50FT



### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		5.8	GHz
VSWR			1.5:1	
Velocity of Propagation		87		%
RF Shielding	90			dB
Capacitance		23.4 [76.77]		pF/ft [pF/m]
Jacket Spark			5,000	Vrms

### Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	0.25	0.5	1	2.5	5.8	GHz
Insertion Loss (Max.)	0.9	1.4	1.9	2.9	4.4	dB

Electrical Specification Notes:

The Insertion Loss data above is based on the performance specifications of the coax cable and connectors used in this assembly. Insertion Loss is estimated as 0.2 dB per right angle connector.

### Mechanical Specifications

#### Size

Length	600 in [15.24 m]
Diameter	0.59 in [14.99 mm]
Weight	6.842 lbs [3.1 Kg]

#### Cable

Cable Type	PPBC-600LL
Impedance	50 Ohms
Inner Conductor Type	Solid
Inner Conductor Material and Plating	Copper Clad Aluminum
Dielectric Type	PE (F)
Number of Shields	2
Shield Layer 1	Aluminum Tape
Shield Layer 2	Tinned Copper Braid
Jacket Material	PE, Black
Jacket Diameter	0.59 in [14.99 mm]
Repeated Minimum Bend Radius	6 in [152.4 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:  
[50 FT Type N to Type N M Right Angle/M Right Angle 600 Series Low Loss Cable Jumper CA600LL049-50FT](#)

50 FT Type N to Type N M Right Angle/M Right Angle  
600 Series Low Loss Cable Jumper

**CA600LL049-50FT**



**Connectors**

Description	Connector 1	Connector 2
Type	N Male Right Angle	N Male Right Angle
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Brass, Gold	Brass, Gold
Dielectric Type	Teflon	Teflon
Body Material and Plating	Brass, Tri-Metal	Brass, Tri-Metal
Coupling Nut Material and Plating	Brass, Nexcote	Brass, Nexcote

**Environmental Specifications**

**Temperature**

Operating Range -40 to +85 deg C

**Compliance Certifications**

**Plotted and Other Data**

Notes:

- Values at 25°C, sea level.

PolyPhaser protects and increases the reliability of global RF communications networks, including transportation, telecommunications, defense, security and industrial applications, with superior RF surge protection technologies including DC Block, DC Pass and Ultra Low PIM. Backed by responsive service and expert technical support PolyPhaser continually expands its product offering and services to serve engineers' urgent needs for RF components in mission critical communication networks.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [50 FT Type N to Type N M Right Angle/M Right Angle 600 Series Low Loss Cable Jumper CA600LL049-50FT](https://www.polyphaser.com/50-ft-type-n-to-type-n-m-right-angle-m-right-angle-600-series-low-loss-cable-jumper-p.aspx)

URL: <https://www.polyphaser.com/50-ft-type-n-to-type-n-m-right-angle-m-right-angle-600-series-low-loss-cable-jumper-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. PolyPhaser reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. PolyPhaser does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and PolyPhaser does not assume any liability arising out of the use of any part or documentation.

CA600LL049-50FT CAD Drawing

