

Type N M/F Bulkhead Coaxial RF Surge Protector, 800MHz
- 2GHz, 750W, IP67, 13 V Max., 500uJ, 40kA, Hybrid



DAS-HY-NMNF-01S

Features

- Surge current 40kA
- Max Power 750W
- Frequency Range from 800MHz to 1000MHZ, 1600MHz to 2000MHz
- N-Type Male connector surge side, N-Type Female connector protected side
- AISG RJ45 Connector
- Waterproof IP67 rated
- VSWR Max 1.1:1
- Insertion Loss Max 0.1dB

Applications

- Cellular communication systems
- Public safety systems
- Emergency response systems
- Industrial

Description

RF surge protector (also known as lightning arrester or surge arrester) DAS-HY-NMNF-01S from PolyPhaser, utilizing a patented hybrid protection technology integrating a silicon avalanche suppression diode (SASD), a Metal Oxide Varistor (MOV) and a gas tube (GT or GDT). This RF surge protector component is manufactured in a coaxial in-line design with wide operating frequency range. All PolyPhaser RF surge protector products are available in stock with same day shipping.

Electrical Specifications

Surge Protector Type
DC Handling

Hybrid
DC Pass

Description	Minimum	Typical	Maximum	Units
Frequency Range	0.8		2	GHz
Impedance		50		Ohms
VSWR			1.1:1	
Insertion Loss			0.1	dB
Operating Voltage (DC)			13	Volts
Input Power, CW			750	Watts
Surge Current IEC 61000-4-5 8/20μs waveform			40	kA
Throughput Energy for 3kA, 8/20μs waveform			500	uJ

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[Type N M/F Bulkhead Coaxial RF Surge Protector, 800MHz - 2GHz, 750W, IP67, 13 V Max., 500uJ, 40kA, Hybrid DAS-HY-NMNF-01S](#)

Type N M/F Bulkhead Coaxial RF Surge Protector, 800MHz
- 2GHz, 750W, IP67, 13 V Max., 500uJ, 40kA, Hybrid



DAS-HY-NMNF-01S

Mechanical Specifications

Weight	1 lbs [453.59 g]
Configuration	
Input Connector	N Male
Output Connector	N Female

Environmental Specifications


Temperature	
Operating Range	-45 to +85 deg C
Storage Range	-45 to +85 deg C
Ingress Protection (IP) Rating	IP67
Humidity	95%

Compliance Certifications

Plotted and Other Data

Notes:

Typical Performance Data




Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[Type N M/F Bulkhead Coaxial RF Surge Protector, 800MHz - 2GHz, 750W, IP67, 13 V Max., 500uJ, 40kA, Hybrid DAS-HY-NMNF-01S](#)

Type N M/F Bulkhead Coaxial RF Surge Protector, 800MHz
- 2GHz, 750W, IP67, 13 V Max., 500uJ, 40kA, Hybrid



DAS-HY-NMNF-01S



PolyPhaser protects and increases the reliability of global RF communications networks, including transportation, telecommunications, defense, security and industrial applications, with superior RF surge protection technologies including DC Block, DC Pass and Ultra Low PIM. Backed by responsive service and expert technical support PolyPhaser continually expands its product offering and services to serve engineers' urgent needs for RF components in mission critical communication networks.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Type N M/F Bulkhead Coaxial RF Surge Protector, 800MHz - 2GHz, 750W, IP67, 13 V Max., 500uJ, 40kA, Hybrid DAS-HY-NMNF-01S](https://www.polyphaser.com/type-n-surge-protector-2ghz-hybrid-das-hy-nmnf-01s-p.aspx)

URL: <https://www.polyphaser.com/type-n-surge-protector-2ghz-hybrid-das-hy-nmnf-01s-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. PolyPhaser reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. PolyPhaser does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and PolyPhaser does not assume any liability arising out of the use of any part or documentation.

Type N M/F Bulkhead Coaxial RF Surge Protector, 800MHz - 2GHz,
750W, IP67, 13 V Max., 500uJ, 40kA, Hybrid

DAS-HY-NMNF-01S CAD Drawing

