

Type N/SMA F/F Bulkhead Coaxial RF Surge Protector, 700MHz
- 2.7GHz, DC Block, 300W, IP67, .5uJ, 18kA, Filter



DSXL-NS

Features

- Surge current of 18kA
- Max Power 300W
- Frequency range from 700 MHz to 2.7 GHz
- Waterproof IP67 rated
- N Female to SMA Female connectors
- DC Block
- VSWR <1.2:1
- Low insertion loss
- CE & RoHS compliant
- Directional

Applications

- Cellular communication systems
- Public safety systems
- Emergency response systems
- Industrial

Description

RF surge protector (also known as lightning arrester or surge arrestor) DSXL-NS from PolyPhaser, utilizing a patented spiral inductor design enables an almost instantaneous response to a lightning surge to protect critical hardware while maintaining the RF performance. This RF surge protector component is manufactured in a coaxial in-line design with wide operating frequency range. All PolyPhaser RF surge protector products are available in stock with same day shipping.

Electrical Specifications

Surge Protector Type DC Handling		Surge Filter DC Block		
Description	Minimum	Typical	Maximum	Units
Frequency Range	0.7		2.7	GHz
Impedance		50		Ohms
VSWR		1.1:1	1.2:1	
Insertion Loss			0.1	dB
Input Power, CW			300	Watts
Surge Current IEC 61000-4-5 8/20μs waveform			18	kA
Throughput Energy for 3kA, 8/20μs waveform			500	nJ

Mechanical Specifications

Width/Diameter 1.11 in [28.19 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[Type N/SMA F/F Bulkhead Coaxial RF Surge Protector, 700MHz - 2.7GHz, DC Block, 300W, IP67, .5uJ, 18kA, Filter DSXL-NS](#)

Type N/SMA F/F Bulkhead Coaxial RF Surge Protector, 700MHz
- 2.7GHz, DC Block, 300W, IP67, .5uJ, 18kA, Filter



DSXL-NS

Height	2.78 in [70.61 mm]
Weight	0.35 lbs [158.76 g]

Configuration

Input Connector	N Female
Output Connector	SMA Female

Environmental Specifications

Temperature

Operating Range	-40 to +85 deg C
Storage Range	-40 to +85 deg C

Ingress Protection (IP) Rating	IP67
Vibration	1G at 5Hz to 100Hz


Compliance Certifications

CE

Plotted and Other Data

Notes:

Typical Performance Data




Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[Type N/SMA F/F Bulkhead Coaxial RF Surge Protector, 700MHz - 2.7GHz, DC Block, 300W, IP67, .5uJ, 18kA, Filter DSXL-NS](#)

Type N/SMA F/F Bulkhead Coaxial RF Surge Protector, 700MHz
- 2.7GHz, DC Block, 300W, IP67, .5uJ, 18kA, Filter



DSXL-NS



PolyPhaser protects and increases the reliability of global RF communications networks, including transportation, telecommunications, defense, security and industrial applications, with superior RF surge protection technologies including DC Block, DC Pass and Ultra Low PIM. Backed by responsive service and expert technical support PolyPhaser continually expands its product offering and services to serve engineers' urgent needs for RF components in mission critical communication networks.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Type N/SMA F/F Bulkhead Coaxial RF Surge Protector, 700MHz - 2.7GHz, DC Block, 300W, IP67, .5uJ, 18kA, Filter DSXL-NS](https://www.polyphaser.com/type-n-sma-surge-protector-2.7ghz-filter-dsxl-ns-p.aspx)

URL: <https://www.polyphaser.com/type-n-sma-surge-protector-2.7ghz-filter-dsxl-ns-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. PolyPhaser reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. PolyPhaser does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and PolyPhaser does not assume any liability arising out of the use of any part or documentation.

Type N/SMA F/F Bulkhead Coaxial RF Surge Protector, 700MHz - 2.7GHz, DC Block, 300W, IP67, .5uJ, 18kA, Filter

DSXL-NS CAD Drawing

