

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLYPHASER, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF POLYPHASER, INC. IS PROHIBITED.

REVISI

DESCRIPTION


DATE

APPROVED

A INITIAL RELEASE

06/03/21

PHOSPODAR



NOTES:

1. FINISH: BLACK POWDER COAT.
2. RECOMMENDED MOUNTING HOLE FOR MATING FASTENER:  
Ø.252 +.002/.000.
3. ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.
4. ALL DIMENSIONS FOR REFERENCE ONLY.
5. COUPLERS SUPPLIED WITH DUST CAPS, NOT SHOWN.

**REGULATORY COMPLIANCE:**

EU RoHS DIRECTIVE (MOST RECENT RELEASED VERSION)

UNLESS OTHERWISE SPECIFIED,  
DIMENSIONS ARE IN INCHES [mm]

OVERALL CABLE LENGTH TOLERANCE:

$\leq 12$  [305] = +1 [25] / -0  
 $> 12$  [305]  $\leq 60$  [1524] = +2 [51] / -0  
 $> 60$  [1524]  $\leq 120$  [3048] = +4 [102] / -0  
 $> 120$  [3048]  $\leq 300$  [7620] = +6 [152] / -0  
 $> 300$  [7620] = +5% / -0

ALL OTHER DIMENSIONAL TOLERANCES:

$.X = \pm .2$  [5]  
 $.XX = \pm .02$  [5]  
 $.XXX = \pm .005$  [1.3]

FRACTIONS  
 $\pm 1/32$   
 ANGLES  $\pm 1^\circ$

THIRD-ANGLE PROJECTION



APPROVALS

DRAWN BY

DMAY

05/26/21

CHECKED BY

PHOSPODAR

06/03/21

APPROVED BY

PHOSPODAR

06/03/21

DATE

DATE

05/26/21

DATE

06/03/21

DATE

06/0