



NOTES:

1. FINISH: BLACK POWDER COAT.
2. RECOMMENDED MOUNTING HOLE FOR MATING FASTENER:  
 $\varnothing .252 +.002/.000$ .
3. ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.
4. ALL DIMENSIONS FOR REFERENCE ONLY.
5. COUPLERS SUPPLIED WITH DUST CAPS, NOT SHOWN.

**REGULATORY COMPLIANCE:**

EU RoHS DIRECTIVE (MOST RECENT RELEASED VERSION)

UNLESS OTHERWISE SPECIFIED,  
DIMENSIONS ARE IN INCHES [mm]

OVERALL CABLE LENGTH TOLERANCE:  
 $\leq 12$  [305]  $= +1$  [25] / -0  
 $> 12$  [305]  $\leq 60$  [1524]  $= +2$  [51] / -0  
 $> 60$  [1524]  $\leq 120$  [3048]  $= +4$  [102] / -0  
 $> 120$  [3048]  $\leq 300$  [7620]  $= +6$  [152] / -0  
 $> 300$  [7620]  $= +5\% / -0$

ALL OTHER DIMENSIONAL TOLERANCES:  
 $.X = \pm .2$  [5] FRACTIONS  
 $.XX = \pm .02$  [5]  $\pm 1/32$   
 $.XXX = \pm .005$  [1.3] ANGLES  $\pm 1^\circ$

THIRD-ANGLE PROJECTION



APPROVALS

DRAWN BY

DMAY

05/26/21

CHECKED BY

PHOSPODAR

06/03/21

APPROVED BY

PHOSPODAR

06/03/21

DATE

DATE