

Type N F/F Bulkhead Coaxial RF Surge Protector, DC - 6GHz,
1000W, IP67, 60 V Max., 2.5mJ, 20kA, Gas Discharge Tube



GTH-NFF-AL

Features

- Surge current of 20kA
- Max Power 1000W(RMS)
- Frequency range from DC to 6 GHz
- N-type Female connectors
- Waterproof IP67 rated
- DC Pass
- Typical VSWR <1.1
- CE & RoHS compliant
- Bi-Directional

Applications

- WiFi
- GPS
- Land mobile radio

Description

RF surge protector (also known as lightning arrester) GTH-NFF-AL from PolyPhaser utilizing a proprietary gas tube surge protection technology protects critical hardware from lightening events while maintaining the RF performance. This RF surge protector component is manufactured in a coaxial in-line design with wide operating frequency range. All PolyPhaser RF surge protector products are available in stock with same day shipping.

Electrical Specifications

Surge Protector Type
DC Handling

Gas Discharge Tube
DC Pass

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		6	GHz
Impedance		50		Ohms
VSWR		1.1:1	1.4:1	
Insertion Loss		0.1	0.25	dB
Operating Voltage (DC)			60	Volts
Operating Current (DC)			10	A
Input Power, CW				
@ 30MHz			1	kWatts
@ 3GHz			300	Watts
Surge Current			20	kA
IEC 61000-4-5 8/20µs waveform				
Throughput Energy			2.5	mJ
Sparkover Voltage (DC)		600 ±20%		Volts

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[Type N F/F Bulkhead Coaxial RF Surge Protector, DC - 6GHz, 1000W, IP67, 60 V Max., 2.5mJ, 20kA, Gas Discharge Tube GTH-NFF-AL](#)

Type N F/F Bulkhead Coaxial RF Surge Protector, DC - 6GHz,
1000W, IP67, 60 V Max., 2.5mJ, 20kA, Gas Discharge Tube



GTH-NFF-AL

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency Range	DC to 3	3 to 4	4 to 6			GHz
VSWR, Typ	1.1:1	1.2:1	1.4:1			
Insertion Loss, Max	0.1	0.1	0.25			dB

Mechanical Specifications

Size

Length	2.2 in [55.88 mm]
Width/Diameter	0.86 in [21.84 mm]
Weight	0.15 lbs [68.04 g]

Configuration

Input Connector	N Female
Output Connector	N Female

Environmental Specifications

Temperature

Operating Range	-55 to +85 deg C
Ingress Protection (IP) Rating	IP67

Compliance Certifications

RoHS Compliant	
CE Compliant	Yes

Plotted and Other Data

Notes:


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[Type N F/F Bulkhead Coaxial RF Surge Protector, DC - 6GHz, 1000W, IP67, 60 V Max., 2.5mJ, 20kA, Gas Discharge Tube GTH-NFF-AL](#)

Type N F/F Bulkhead Coaxial RF Surge Protector, DC - 6GHz,
1000W, IP67, 60 V Max., 2.5mJ, 20kA, Gas Discharge Tube



GTH-NFF-AL

Typical Performance Data




Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[Type N F/F Bulkhead Coaxial RF Surge Protector, DC - 6GHz, 1000W, IP67, 60 V Max., 2.5mJ, 20kA, Gas Discharge Tube GTH-NFF-AL](#)

Type N F/F Bulkhead Coaxial RF Surge Protector, DC - 6GHz,
1000W, IP67, 60 V Max., 2.5mJ, 20kA, Gas Discharge Tube



GTH-NFF-AL



PolyPhaser protects and increases the reliability of global RF communications networks, including transportation, telecommunications, defense, security and industrial applications, with superior RF surge protection technologies including DC Block, DC Pass and Ultra Low PIM. Backed by responsive service and expert technical support PolyPhaser continually expands its product offering and services to serve engineers' urgent needs for RF components in mission critical communication networks.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Type N F/F Bulkhead Coaxial RF Surge Protector, DC - 6GHz, 1000W, IP67, 60 V Max., 2.5mJ, 20kA, Gas Discharge Tube GTH-NFF-AL](https://www.polyphaser.com/type-n-surge-protector-6ghz-4ghz-gas-discharge-tube-gth-nff-al-p.aspx)

URL: <https://www.polyphaser.com/type-n-surge-protector-6ghz-4ghz-gas-discharge-tube-gth-nff-al-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. PolyPhaser reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. PolyPhaser does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and PolyPhaser does not assume any liability arising out of the use of any part or documentation.

Type N F/F Bulkhead Coaxial RF Surge Protector, DC - 6GHz, 1000W,
IP67, 60 V Max., 2.5mJ, 20kA, Gas Discharge Tube

GTH-NFF-AL CAD Drawing



T-Rev.D