

Type N F/M Coaxial RF Surge Protector, 50MHz - 700MHz, DC Block, 500W, 1mJ, 50kA, Blocking Cap, Bracket Up, Hole Mount



## IS-B50HN-C1-ME

### Features

- Surge current of 50kA
- Max Power 500W
- Frequency range from 50 MHz to 700 MHz
- N Female to N Male connectors
- VSWR 1.2:1
- Multi-strike capability
- CE & RoHS compliant

### Applications

- HF, UHF and VHF radios
- Ham radios
- Remote industrial monitoring

### Description

RF surge protector (also known as lightning arrester or surge arrester) IS-B50HN-C1-ME from PolyPhaser, integrating a RF blocking capacitor with a gas tube (GT or GDT). This RF surge protector component is manufactured in a coaxial in-line design with wide operating frequency range. All PolyPhaser RF surge protector products are available in stock with same day shipping.

### Electrical Specifications

Surge Protector Type	Blocking Cap and Gas Tube			
DC Handling	DC Block			
Description	Minimum	Typical	Maximum	Units
Frequency Range	50		700	MHz
Impedance		50		Ohms
VSWR		1.1:1	1.2:1	
Insertion Loss			0.1	dB
Input Power, CW			500	Watts
500W @ VHF Band				
250W @ UHF Band				
Surge Current			50	kA
Turn On Voltage		1,200 20%		Volts
Throughput Energy			1	mJ
for 6kA/3kA 8/20μs waveform				

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:  
[Type N F/M Coaxial RF Surge Protector, 50MHz - 700MHz, DC Block, 500W, 1mJ, 50kA, Blocking Cap, Bracket Up, Hole Mount IS-B50HN-C1-ME](#)

Type N F/M Coaxial RF Surge Protector, 50MHz - 700MHz, DC Block, 500W, 1mJ, 50kA, Blocking Cap, Bracket Up, Hole Mount



## IS-B50HN-C1-ME

### Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency Range	0.05 to 0.06	0.06 to 0.7				GHz
VSWR, Typ	1.2:1	1.1:1				

### Mechanical Specifications

Height	2.25 in [57.15 mm]
Weight	1 lbs [453.59 g]

Configuration	
Input Connector	N Female
Output Connector	N Male

### Environmental Specifications

Temperature	
Operating Range	-45 to +50 deg C
Storage Range	-45 to +85 deg C
Ingress Protection (IP) Rating	None
Vibration	1G at 5Hz to 100Hz

### Compliance Certifications

CE Compliant	Yes
UL	UL497E

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:  
[Type N F/M Coaxial RF Surge Protector, 50MHz - 700MHz, DC Block, 500W, 1mJ, 50kA, Blocking Cap, Bracket Up, Hole Mount IS-B50HN-C1-ME](#)

Type N F/M Coaxial RF Surge Protector, 50MHz - 700MHz, DC Block, 500W, 1mJ, 50kA, Blocking Cap, Bracket Up, Hole Mount



## IS-B50HN-C1-ME

### Plotted and Other Data

Notes:

PolyPhaser protects and increases the reliability of global RF communications networks, including transportation, telecommunications, defense, security and industrial applications, with superior RF surge protection technologies including DC Block, DC Pass and Ultra Low PIM. Backed by responsive service and expert technical support PolyPhaser continually expands its product offering and services to serve engineers' urgent needs for RF components in mission critical communication networks.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Type N F/M Coaxial RF Surge Protector, 50MHz - 700MHz, DC Block, 500W, 1mJ, 50kA, Blocking Cap, Bracket Up, Hole Mount IS-B50HN-C1-ME](#)

URL: <https://www.polyphaser.com/type-n-surge-protector-blocking-cap-gas-tube-is-b50hn-c1-me-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. PolyPhaser reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. PolyPhaser does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and PolyPhaser does not assume any liability arising out of the use of any part or documentation.

Type N F/M Coaxial RF Surge Protector, 50MHz - 700MHz, DC Block, 500W, 1mJ, 50kA, Blocking Cap, Bracket Up, Hole Mount

**IS-B50HN-C1-ME CAD Drawing**

