

Type N F/M Bulkhead Coaxial RF Surge Protector, 1.8GHz - 6GHz, DC Block, 10W, IP67, .5uJ, 18kA, Filter



LSXL-ME

Features

- Surge current of 18kA
- Max Power 10W
- Frequency range from 1.8 to 6 GHz
- Waterproof IP67 rated
- N Female to N Male connectors
- DC Block
- VSWR <1.3:1
- Low insertion loss
- CE & RoHS compliant
- Directional

Applications

- Cellular communication systems
- Public safety systems
- Emergency response systems
- Industrial

Description

RF surge protector (also known as lightning arrester) LSXL-ME from PolyPhaser utilizing a patented spiral inductor design enables an almost instantaneous response to a lightning surge to protect critical hardware while maintaining the RF performance. This RF surge protector component is manufactured in a coaxial in-line design with wide operating frequency range. All PolyPhaser RF surge protector products are available in stock with same day shipping.

Electrical Specifications

Surge Protector Type
DC Handling

Surge Filter
DC Block

Description	Minimum	Typical	Maximum	Units
Frequency Range	1.8		6	GHz
Impedance		50		Ohms
Input Power, CW			10	Watts
Surge Current			18	kA
Throughput Energy for 3kA @ 8/20µs waveform			500	nJ

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[Type N F/M Bulkhead Coaxial RF Surge Protector, 1.8GHz - 6GHz, DC Block, 10W, IP67, .5uJ, 18kA, Filter LSXL-ME](#)

Type N F/M Bulkhead Coaxial RF Surge Protector, 1.8GHz - 6GHz, DC Block, 10W, IP67, .5uJ, 18kA, Filter



LSXL-ME

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency Range	1.8 to 3.8		4.2 to 6			GHz
VSWR, Typ	1.2:1		1.2:1			
VSWR, Max	1.3:1		1.3:1			
Insertion Loss, Max	0.2		0.2			dB

Mechanical Specifications

Size

Length	2.8 in [71.12 mm]
Width/Diameter	1.12 in [28.45 mm]
Weight	0.4 lbs [181.44 g]

Configuration

Input Connector	N Female
Output Connector	N Male

Environmental Specifications

Temperature

Operating Range	-40 to +85 deg C
Ingress Protection (IP) Rating	IP67
Vibration	1G at 5Hz to 100Hz

Compliance Certifications

RoHS
CE

Plotted and Other Data

Notes:


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[Type N F/M Bulkhead Coaxial RF Surge Protector, 1.8GHz - 6GHz, DC Block, 10W, IP67, .5uJ, 18kA, Filter LSXL-ME](#)

Type N F/M Bulkhead Coaxial RF Surge Protector, 1.8GHz - 6GHz, DC Block, 10W, IP67, .5uJ, 18kA, Filter



LSXL-ME

Typical Performance Data




Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[Type N F/M Bulkhead Coaxial RF Surge Protector, 1.8GHz - 6GHz, DC Block, 10W, IP67, .5uJ, 18kA, Filter LSXL-ME](#)

Type N F/M Bulkhead Coaxial RF Surge Protector, 1.8GHz
- 6GHz, DC Block, 10W, IP67, .5uJ, 18kA, Filter



LSXL-ME



PolyPhaser protects and increases the reliability of global RF communications networks, including transportation, telecommunications, defense, security and industrial applications, with superior RF surge protection technologies including DC Block, DC Pass and Ultra Low PIM. Backed by responsive service and expert technical support PolyPhaser continually expands its product offering and services to serve engineers' urgent needs for RF components in mission critical communication networks.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Type N F/M Bulkhead Coaxial RF Surge Protector, 1.8GHz - 6GHz, DC Block, 10W, IP67, .5uJ, 18kA, Filter LSXL-ME](https://www.polyphaser.com/type-n-surge-protector-6ghz-filter-lsxl-me-p.aspx)

URL: <https://www.polyphaser.com/type-n-surge-protector-6ghz-filter-lsxl-me-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. PolyPhaser reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. PolyPhaser does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and PolyPhaser does not assume any liability arising out of the use of any part or documentation.

LSXL-ME CAD Drawing

Technical drawing of the LSXL-ME surge protector. The drawing includes a front view with dimensions: total height 2.80 [71.1], mounting hole diameter $\phi 1.12$ [28.3], and a distance of 1.14 [29] from the top of the main body to the center of the mounting hole. The main body is 1.00 [25.4] high. The top view shows a diameter of .53 [13.5]. A perspective view shows the device with a threaded section labeled 5/8-24 UNEF-2A. The device label includes: SURGE, LSXL-ME PolyPhaser, 1.8GHz to 6.0GHz, 4.3GHz to 6.0GHz, U.S. PATENT NO. 8,001,228, 8,118,227, 8,294,861, MADE IN U.S.A., and PROTECTED. A hardware kit list is provided below the drawing.

HARDWARE KIT INCLUDES:

QTY	DESCRIPTION
1	NUT 5/8-24 303 HEX SS
1	WASHER 5/8 410 SS
1	SILICONE O-RING 019

ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.

UNLESS OTHERWISE SPECIFIED, LEADING DIMENSIONS ARE IN INCHES, DIMENSIONS IN [] ARE MILLIMETERS.

TOLERANCES: FRACTIONS: ± 1/32 XX: ± .03 ANGLES: ± 1° XXX: ± .010

NOTE: THIS DRAWING MAY BE MODIFIED WITHOUT NOTICE. THIS DOCUMENT IS THE PROPERTY OF POLYPHASER CORP. ALL RIGHTS RESERVED.

THIRD-ANGLE PROJECTION

PolyPhaser

CELL FILTER
2GHZ-6GHZ

SIZE: A CAGE: 30992 PROD CAT: RFP DRAWING NUMBER: LSXL-ME REV: A

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.