


8 7 6 5 4 3 2 1
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLYPHASER, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF POLYPHASER, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	8/6/21	PHOSPODAR



WIRING MAP	
MPO FIBER #	ST COLOR
1	BLUE
2	ORANGE
3	GREEN
4	BROWN
5	GRAY
6	WHITE
7	RED
8	BLACK
9	YELLOW
10	PURPLE
11	ROSE
12	AQUA

PART NUMBER	FIBER MODE	LENGTH METERS [FEET]	BREAKOUT METERS [FEET]
MFO-M12M5-STR-1	50/125 MULTIMODE OM5	1.0 [3.28]	.61 [2.0]
MFO-M12M5-STR-3	50/125 MULTIMODE OM5	3.0 [9.84]	.61 [2.0]
MFO-M12M5-STR-5	50/125 MULTIMODE OM5	5.0 [16.40]	.61 [2.0]
MFO-M12M5-STR-10	50/125 MULTIMODE OM5	10.0 [32.81]	.61 [2.0]

UNLESS OTHERWISE SPECIFIED,
DIMENSIONS ARE IN INCHES [mm]


OVERALL CABLE LENGTH TOLERANCE:
 ≤ 12 [305] = $+1$ [25] / -0
 > 12 [305] ≤ 60 [1524] = $+2$ [51] / -0
 > 60 [1524] ≤ 120 [3048] = $+4$ [102] / -0
 > 120 [3048] ≤ 300 [7620] = $+6$ [152] / -0
 > 300 [7620] = $+5\%$ / -0

ALL OTHER DIMENSIONAL TOLERANCES:

$.X = \pm .2$ [5]
 $.XX = \pm .02$ [5]
 $.XXX = \pm .005$ [1.3]

FRACTIONS
 $\pm 1/32$
 ANGLES $\pm 1^\circ$

THIRD-ANGLE PROJECTION



CONFIGURATION DETAILS OF
UNDIMENSIONED FEATURES
MAY VARY

COLOR VARIATIONS
MAY OCCUR

SIZE	CAGE CODE	ITEM NO.	REV.
A	30992	MFO-M12M5-STR	A
SCALE: NONE	CAD FILE: MFO-M12M5-STR.SLDDRW	SHEET 1 OF 1	

REGULATORY COMPLIANCE:

EU RoHS DIRECTIVE (MOST RECENT RELEASED VERSION)

PolyPhaser
an INFINITE brand

10701 Airport Road,
Hayden, ID 83835
Phone: 1.208.635.6400
Fax: 1.208.955.2041

FIBER OPTICS

PRODUCT DESCRIPTION
Fan-Out Cable, MPO Male to ST, 12 Fibers,
OM5, OFNR Jacket, Lime Green