

8 7 6 5 4 3 2 1

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLYPHASER, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF POLYPHASER, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	8/6/21	PHOSPODAR

D

D

C

C


B

B

A

A

WIRING MAP	
MPO FIBER #	LC COLOR
1	BLUE
2	ORANGE
3	GREEN
4	BROWN
5	GRAY
6	WHITE
7	RED
8	BLACK
9	YELLOW
10	PURPLE
11	ROSE
12	AQUA
13	BLUE
14	ORANGE
15	GREEN
16	BROWN
17	GRAY
18	WHITE
19	RED
20	BLACK
21	YELLOW
22	PURPLE
23	ROSE
24	AQUA



PART NUMBER	FIBER MODE	LENGTH METERS [FEET]	BREAKOUT METERS [FEET]
MFO-M24M3-FLCR-1	50/125 MULTIMODE OM3	1.0 [3.28]	.61 [2.0]
MFO-M24M3-FLCR-3	50/125 MULTIMODE OM3	3.0 [9.84]	.61 [2.0]
MFO-M24M3-FLCR-5	50/125 MULTIMODE OM3	5.0 [16.40]	.61 [2.0]
MFO-M24M3-FLCR-10	50/125 MULTIMODE OM3	10.0 [32.81]	.61 [2.0]

UNLESS OTHERWISE SPECIFIED,
DIMENSIONS ARE IN INCHES [mm]

OVERALL CABLE LENGTH TOLERANCE:

 $\leq 12 [305] = +1 [25] / -0$
 $> 12 [305] \leq 60 [1524] = +2 [51] / -0$
 $> 60 [1524] \leq 120 [3048] = +4 [102] / -0$
 $> 120 [3048] \leq 300 [7620] = +6 [152] / -0$
 $> 300 [7620] = +5\% / -0$

ALL OTHER DIMENSIONAL TOLERANCES:

 $.X = \pm .2 [5]$ FRACTIONS
 $.XX = \pm .02 [5]$
 $.XXX = \pm .005 [1.3]$ ANGLES $\pm 1^\circ$


APPROVALS

DRAWN BY

CHECKED BY

APPROVED BY

DATE

DMAY

PHOSPODAR

PHOSPODAR

CATEGORY

PolyPhaser
an INFINIT brand

10701 Airport Road,
Hayden, ID 83835
Phone: 1.208.635.6400
Fax: 1.208.955.2041

FIBER OPTICS

CONFIGURATION DETAILS OF
UNDIMENSIONED FEATURES
MAY VARY

COLOR VARIATIONS
MAY OCCUR

PRODUCT DESCRIPTION
Fan-Out Cable, MPO Male to Flex-boot LC,
24 Fibers, OM3, OFNR Jacket, Aqua

SIZE A CAGE CODE 30992 ITEM NO. MFO-M24M3-FLCR REV. A
SCALE: NONE CAD FILE: MFO-M24M3-FLCR.SLDDRW SHEET 1 OF 1

REGULATORY COMPLIANCE:

EU RoHS DIRECTIVE (MOST RECENT RELEASED VERSION)