


8 7 6 5 4 3 2 1

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLYPHASER, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF POLYPHASER, INC. IS PROHIBITED.




WIRING MAP			
PAIR	LC	1X12	REF DES
P1	1	1	J1
	12	12	
P2	2	2	
	11	11	
P3	3	3	
	10	10	
P4	4	4	
	9	9	
P5	5	5	
	8	8	
P6	6	6	
	7	7	

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	08/16/21	PHOSPODAR



PART NUMBER	METERS (FEET)
MPF12M4-20LCR-1	1.0 (3.28)
MPF12M4-20LCR-3	3.0 (9.84)
MPF12M4-20LCR-5	5.0 (16.40)
MPF12M4-20LCR-10	10.0 (32.81)

- NOTES:
- CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.
  - CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN A CLEAR POLY BAG AND LABELED.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm]		APPROVALS		DATE		<div> an INFINITI brand</div> <div>10701 Airport Road, Hayden, ID 83835 Phone: 1.208.635.6400 Fax: 1.208.955.2041</div>	
OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0  ALL OTHER DIMENSIONAL TOLERANCES: .X = ± .2 [5]      FRACTIONS ± 1/32 .XX = ± .02 [.5]      ANGLES ± 1° .XXX = ± .005 [.13]		DRAWN BY DFRISIELLO		08/16/2021			
		CHECKED BY PHOSPODAR		08/16/2021			
		APPROVED BY PHOSPODAR		08/16/2021			
<div>THIRD-ANGLE PROJECTION</div> <div></div>		CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY		CATEGORY		FIBER OPTICS	
				PRODUCT DESCRIPTION		MPO w/o pins to LC fanout fiber, 2.0mm diameter, 12 fiber, OM4 50/125um	
<div>THIRD-ANGLE PROJECTION</div> <div></div>		COLOR VARIATIONS MAY OCCUR		SIZE <b>A</b>	CAGE CODE <b>30992</b>	ITEM NO. MPF12M4-20LCR	REV. <b>A</b>
				SCALE: NONE		CAD FILE: MPF12M4-20LCR.SLDDRW	