

Passive CWDM, Field Cassette Mux, 8 ch w/ 20nm spacing,
start 1470nm, 1.0m 900um buffer, w/ pass



PCFCM-8C20P-1470

Features

- Passive
- CWDM
- 20nm spacing
- Rugged Field Cassette (100x80x10mm)
- Single Fiber Mux
- 8 Channels
- Starting with channel 1471nm
- 1m 900um fiber leads
- Pass fiber for unused CWDM channels
- industrial temperature (-40c ~ 85c)

Applications

- Single Mode Fiber Networking
- Single Fiber
- Mux function
- Metro transport
- Regional Distribution
- Outside Plant (OSP) Operation

Description

The PolyPhaser PCFCM-8C20P-1470 is a CWDM Passive Filter with 8 CWDM Channels. The PolyPhaser PCFCM-8C20P-1470 is a 120x85x20mm field cassette filter with mux functionality. The PolyPhaser PCFCM-8C20P-1470 is rated for industrial temperature function (-40c to +85c) for applications such as outside plant installation. The PolyPhaser PCFCM-8C20P-1470 has 8 channels: 1471, 1491, 1511, 1531, 1551, 1571, 1591, and 1691nm, starting with 1471nm and with 20nm spacing. The PolyPhaser PCFCM-8C20P-1470 has 1 meter 900um buffer fiber leads. The PolyPhaser PCFCM-8C20P-1470 is a single fiber filter for muxing channels into a COM signal. The PolyPhaser PCFCM-8C20P-1470 includes the optional Pass fiber for carrying the CWDM channels not present in this filter. PolyPhaser produces the high quality passive filters that your business can rely on. With products continually in stock and same-day shipping, our expert technical support and knowledgeable sales team can get you to the right parts for the job.

Configuration

Connector Type	900um Bare Fiber (1M)
Number of Channels	8
Module Function	Mux
Filter Type	CWDM

Filter Specifications

Description	Minimum	Typical	Maximum	Units
Operating Wavelength	1260		1635	nm
Pass Port Wavelength	1,271		1,611	nm
Pass Port Insertion Loss			2.8	dB
Pass Band	6.5			nm
Pass Band Ripple			0.5	dB
Center Wavelength (Channel)	1,471		1,611	nm
Channel Spacing		20		nm
Channel Insertion Loss			3	dB
Return Loss	45			dB
Directivity			50	dB
PDL			0.25	dB

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[Passive CWDM, Field Cassette Mux, 8 ch w/ 20nm spacing, start 1470nm, 1.0m 900um buffer, w/ pass PCFCM-8C20P-1470](#)

Passive CWDM, Field Cassette Mux, 8 ch w/ 20nm spacing,
start 1470nm, 1.0m 900um buffer, w/ pass



PCFCM-8C20P-1470

PMD	0.2	PS
Power Handling	300	mW
IL Thermal Stability	0.005	dB/degC
Wavelength Thermal Stability	0.002	nm/degC

Weight 0.2 lbs [90.72 g]

Environmental Specifications

Temperature

Operating Range -40 to +85 deg C
Storage Range -40 to +85 deg C

Humidity 5-95 %RH

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

PolyPhaser protects and increases the reliability of global RF communications networks, including transportation, telecommunications, defense, security and industrial applications, with superior RF surge protection technologies including DC Block, DC Pass and Ultra Low PIM. Backed by responsive service and expert technical support PolyPhaser continually expands its product offering and services to serve engineers' urgent needs for RF components in mission critical communication networks.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Passive CWDM, Field Cassette Mux, 8 ch w/ 20nm spacing, start 1470nm, 1.0m 900um buffer, w/ pass PCFCM-8C20P-1470](#)

URL: <https://www.polyphaser.com/passive-cwdm-field-cassette-mux-8-ch-w-20nm-spacing-start-1470nm-1.0m-900um-buffer-w-pass-pcfc-8c20p-1470-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. PolyPhaser reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. PolyPhaser does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and PolyPhaser does not assume any liability arising out of the use of any part or documentation.

3 PCFCM-8C20P-1470 REV 1 | © 2020 Infinite Electronics, Inc. PolyPhaser is a registered trademark of Infinite Electronics, Inc.
+1 800 882 9110 | [PolyPhaser.com](https://www.polyphaser.com)