

Passive CWDM, 1 RU 19" Rack Mount Mux/Demux, 16 Ch Custom (skip 1391-1411nm) w/20nm spacing, start ch 1270nm, LC/UPC w/MON (1%)

PCWDM-RMMDM-162027

Features

- Passive
- CWDM
- 20nm spacing
- 19" Rack Mount
- Two Fiber Mux & Demux Combo
- 16 Channels (skipping 1391&1411nm)
- Starting with channel 1271nm
- LC/UPC connectors
- 1% Monitor option

Applications

- Single Mode Fiber Networking
- Dual Fiber
- side by side mux and demux functions
- Metro transport
- Regional Distribution
- Inside Plant (ISP) Operation

Description

The PolyPhaser PCWDM-RMMDM-162027 is a CWDM Passive Filter with 16 CWDM Channels. The PolyPhaser PCWDM-RMMDM-162027 is a 1RU 19" Rack Mount filter with Combo Mux and DeMux functionality. The PolyPhaser PCWDM-RMMDM-162027 has 16 channels: 1271, 1291, 1311, 1331, 1351, 1371, 1431, 1451, 1471, 1491, 1511, 1531, 1551, 1571, 1591, and 1611nm (skipping 1391 and 1411nm) starting with 1271nm and with 20nm spacing. The PolyPhaser PCWDM-RMMDM-162027 has LC/UPC connectors and has Monitor port option on Mux and Demux. The PolyPhaser PCWDM-RMMDM-162027 is a dual fiber filter with one sending muxed signal and the other receiving a composite signal for demuxing. PolyPhaser produces the high quality passive filters that your business can rely on. With products continually in stock and same-day shipping, our expert technical support and knowledgeable sales team can get you to the right parts for the job.

Configuration

Connector Type	LC/UPC
Number of Channels	16
Module Function	Mux/DeMux
Filter Type	CWDM

Filter Specifications

Description	Minimum	Typical	Maximum	Units
Operating Wavelength	1260		1635	nm
Pass Band	6.5			nm
Pass Band Ripple			0.5	dB
Center Wavelength (Channel)	1,271		1,611	nm
Channel Spacing		20		nm
Channel Insertion Loss			4	dB
Return Loss	45			dB
Directivity			50	dB
PDL			0.25	dB
PMD			0.2	PS
Power Handling			300	mW

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[Passive CWDM, 1 RU 19" Rack Mount Mux/Demux, 16 Ch Custom \(skip 1391-1411nm\) w/20nm spacing, start ch 1270nm, LC/UPC w/MON \(1%\) PCWDM-RMMDM-162027](#)

Passive CWDM, 1 RU 19" Rack Mount Mux/Demux, 16 Ch Custom (skip 1391-1411nm) w/20nm spacing, start ch 1270nm, LC/UPC w/MON (1%)

PCWDM-RMMDM-162027

Non-Adjacent Channel Isolation	0.2		dB
Channel to Monitor Port IL		25	dB
COM to Monitor Port IL		23	dB
IL Thermal Stability		0.005	dB/degC
Wavelength Thermal Stability		0.002	nm/degC

Weight 7.5 lbs [3.4 kg]

Environmental Specifications

Temperature

Operating Range -20 to +65 deg C

Storage Range -40 to +85 deg C

Humidity 5-98 %RH

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

PolyPhaser protects and increases the reliability of global RF communications networks, including transportation, telecommunications, defense, security and industrial applications, with superior RF surge protection technologies including DC Block, DC Pass and Ultra Low PIM. Backed by responsive service and expert technical support PolyPhaser continually expands its product offering and services to serve engineers' urgent needs for RF components in mission critical communication networks.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Passive CWDM, 1 RU 19" Rack Mount Mux/Demux, 16 Ch Custom \(skip 1391-1411nm\) w/20nm spacing, start ch 1270nm, LC/UPC w/MON \(1%\) PCWDM-RMMDM-162027](#)

URL: <https://www.polyphaser.com/passive-cwdm-1-ru-19-rack-mount-mux-demux-16-ch-custom-skip-1391-1411nm-w-20nm-spacing-start-ch-1270nm-lc-upc-w-mon-1-pcwdm-rmmdm-162027-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. PolyPhaser reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. PolyPhaser does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and PolyPhaser does not assume any liability arising out of the use of any part or documentation.

PCWDM-RMMDM-162027 CAD Drawing

