![PolyPhaser an INFINITE brand]

Fiber Enclosure Rack Mount 1U (1.75") 24 Simplex SC/
APC Adapters and 24 SC/APC 0.9mm Pigtails

PFPP-SL01-24SCA

Features

- 24 Simplex SC/APC Couplers Installed along with 24 SC/APC 0.9mm Pigtails
- 1U (1.75") 19 Inch Rack Mount design
- Cable Management Tray designed to securely and safely hold your fiber strands

- Sliding tray design allows for easy access to your fiber connections even while installed in a standard 19 inch rack
- TIA/EIA-568-B.3 compliant

Applications

- FTTH Access Networks
- Telecommunication Networks
- CATV Networks

- Data Communications Networks
- Local Area Networks

Description

This 19 Inch Rack Mount Fiber Enclosure, the PFPP-SL01-24SCA, and its low profile 1U (1.75") design comes with 24 Simplex SC/APC couplers pre-installed along with 24 SC/APC 0.9mm pigtails. Ideal for fiber termination in your network closet, the slide out tray provides easy access to your fiber optic connections.

Mechanical Specifications
Size

Outer Height	1.75 in	[44.45 mm]
Outer Width	19 in	[482.6 mm]
Outer Depth	9.5 in	[241.3 mm]
Weight	8.8 lbs	[3.99 kg]
Enclosure Material	SPCC Steel Cold Rolled Steel	
Material Thickness	16 Gauge	

Environmental Specifications

Operating Temperature	-40 to 60 deg C

Low PIM. Backed by responsive service and expert technical support PolyPhaser continually expands its product offering and services to serve engineers' urgent needs for RF components in mission critical communication networks.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Fiber Enclosure Rack Mount 1U (1.75") 24 Simplex SC/APC Adapters and 24 SC/APC 0.9mm Pigtails PFPP-SL01-24SCA

URL: https://www.polyphaser.com/PFPP-SL01-24SCA-p.aspx

Fiber Enclosure Rack Mount 1U (1.75") 24 Simplex SC/APC Adapters and 24 SC/APC 0.9mm Pigtails

PFPP-SL01-24SCA CAD Drawing

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	01/07/2021	TOZA

THIRD ANGLE PROJECTION

THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF POLYPHASER, INC ALL RIGHTS RESERVED.

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [ ] ARE MILLIMETERS

TOLERANCES:
X = ± .2 [5.08]
.XX = ± .02 [.51]
.XXX = ± .005 [.13]

FRACTIONS ± 1/32
ANGLES ± 1°

CABLE LENGTH (L) TOLERANCES:
12 [305] ≤ L ≤ 12 [305] = +1 [25] / -0
12 [305] < L ≤ 60 [1524] = +2 [51] / -0
60 [1524] < L ≤ 120 [3048] = +4 [1.21] / -0
120 [3048] < L ≤ 300 [7620] = +6 [152] / -0
300 [7620] < L = +5% / L / -0

ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.

DIMENSIONS ARE FOR REFERENCE ONLY.
DIMENSIONS ARE SHOWN IN MILLIMETERS.

482
465
430
240
44