

Wall Mount Fiber Enclosure, Single Mode SC/UPC,
72 Coupler Ports and Pigtails, SPCC Steel, Gray



PP-WM72SC

Features

- Painted Carbon Steel
- Low Profile Wall Mounted Fiber Enclosure
- Supports Fiber Splices to 72 Simplex SC couplers
- Routing guides to limit bend radius and enhance strain-relief control
- Spring loaded press-pull button lock latch

Applications

- FTTH Access Networks
- Telecommunication Networks
- CATV Networks
- Data Communications Networks
- Local Area Networks

Description

The Polyphaser PP-WM72SC is an indoor, wall-mounted cross-connect enclosure for fiber optic distribution management. The PP-WM72SC is ideal for end terminations of fiber optic runs into residential and commercial buildings. The PP-WM72SC comes with 72 SC simplex coupler ports installed with 72x SC/UPC single mode pigtails ready for splicing. In addition to the fiber pigtails and couplers, the PP-WM72SC comes with a fiber optic splice tray & cable management guides that help maintain a bend radius greater than 1.6in [40mm].

The Polyphaser PP-WM72SC has a wall-mounted configuration that permits fiber management, connectivity and distribution of 72 SC incoming fiber optic cable channels. All the cross connect tasks of splicing, termination and interconnection to your plant, backbone and in-building fiber can be performed in the enclosure, thereby greatly protecting and simplifying your installations. The Polyphaser PP-WM72SC enclosure is SPCC steel offering protection from damage in stand-alone locations and in network closets. It has a single door, and the cable entry points are fully protected and easily accessible.

Mechanical Specifications

Size

Outer Height	17.91 in	[454.91 mm]
Outer Width	15.95 in	[405.13 mm]
Outer Depth	5.91 in	[150.11 mm]
Weight	22 lbs	[9.98 kg]
Enclosure Material	SPCC Steel	

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[Wall Mount Fiber Enclosure, Single Mode SC/UPC, 72 Coupler Ports and Pigtails, SPCC Steel, Gray PP-WM72SC](#)

Wall Mount Fiber Enclosure, Single Mode SC/UPC, 72 Coupler Ports and Pigtailed, SPCC Steel, Gray



PP-WM72SC

Environmental Specifications

Temperature Continuous

-40 to 60deg C

PolyPhaser protects and increases the reliability of global RF communications networks, including transportation, telecommunications, defense, security and industrial applications, with superior RF surge protection technologies including DC Block, DC Pass and Ultra Low PIM. Backed by responsive service and expert technical support PolyPhaser continually expands its product offering and services to serve engineers' urgent needs for RF components in mission critical communication networks.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Wall Mount Fiber Enclosure, Single Mode SC/UPC, 72 Coupler Ports and Pigtailed, SPCC Steel, Gray PP-WM72SC](#)

URL: <https://www.polyphaser.com/fiber-enclosure-wall-mount-with-72-sc-upc-single-mode-couplers-pigtails-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. PolyPhaser reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. PolyPhaser does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and PolyPhaser does not assume any liability arising out of the use of any part or documentation.

Polyphaser CAD Drawing

