




THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLYPHASER, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF POLYPHASER, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	09/21/21	PHOSPODAR



PARAMETER	SPECIFICATION
FIBER TYPE	OM4
CONNECTOR TYPE	LC/UPC
ADAPTER TYPE	LC ADAPTER, AQUA

ITEM NUMBER	SPLIT	WAVELENGTHS	INSERTION LOSS PER SPLIT	PDL	RETURN LOSS	DIRECTIVITY
		nm	dB	dB	dB	dB
PTAP-5050-M4LC-LGX	50/50	850±20	3.9/3.9	≤ 0.15	≥ 50	≥ 55
PTAP-6040-M4LC-LGX	60/40		2.9/4.9			
PTAP-7030-M4LC-LGX	70/30		2.2/6.2			
PTAP-9802-M4LC-LGX	98/2		0.5/19.1			

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm]		APPROVALS		DATE		<div> an INFINITO brand</div> <div>10701 Airport Road, Hayden, ID 83835 Phone: 1.208.635.6400 Fax: 1.208.955.2041</div>	
OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0		DRAWN BY		09/21/21			
ALL OTHER DIMENSIONAL TOLERANCES: .X = .2 [5] FRACTIONS .XX = .02 [.5] ± 1/32 .XXX = .005 [.13] ANGLES ± 1°		CHECKED BY JLABOY		09/21/21			
THIRD-ANGLE PROJECTION 		APPROVED BY PHOSPODAR		09/21/21			
CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY		CATEGORY		FIBER OPTIC			
COLOR VARIATIONS MAY OCCUR		PRODUCT DESCRIPTION PASSIVE OPTICAL TAP, MMF OM4 LC CONNECTORS					
SIZE A		CAGE CODE 30992		ITEM NO. PTAP-XXXX-M4LC-LGX		REV. A	
SCALE: NONE		CAD FILE: ptap-xxxx-m4lc-lgx.SLDDRW				SHEET 1 OF 1	